

Product's Features

- The main body is made of aluminum die-cast, white
- The diffuser is anodized aluminum
- Anti-glare lighting design
- High temperature flame retardant lampholders, terminals and wires

Applications

- Office, shopping malls, schools, factories and so on

Technical parameters

- type of light source : LED
- Lamp power : 5-35W
- Electrical Type: Switching Power Supply
- Working power supply : 220V~240V , 50Hz
- Color temperature : 3000-6000k
- Insulation Grade : Class 1
- Safety Standards : IEC598
- Color rendering index: Ra ≥ 80
- Lumen value: 70-100LM / W
- Life expectancy: 5 years
- Luminous angle:15°、24°、38°、60°



Order Guide :

Model	Number	Power Qty	Dimension	Design	Electrical appliances	reflector	installation	Choose to match
GHCE	012			DA		AM	EI	
GHCE			62 Φ62 H 85 86 Φ86 H 115 110 Φ110 H 140 140 Φ140 H 155 168 Φ168 H 200 198 Φ198 H 210	DA Die-cast aluminum	PS Switching power supply Please refer to the power supply technical information	AM Mirror aluminum	EI Embedded installation	OP power cable ED Emergency devices (The emergency device is installed outside the lamp body) Duration time:≥180min Battery:Li-ion : 6600mAh Emergency power:16W Charing time:≥24HR Working temperature : -10°C~+50°C Size:260*76*70mm
								Voltage 220 220-240V

备注：可按客户特殊要求生产
Remark:compliance with the requirement of the buyer



型号	系列号	光源功率(W)	直径(mm)	高度(mm)
GHCE	012	5	62	85
GHCE	012	9	86	115
GHCE	012	12	86	115
GHCE	012	16	110	140
GHCE	012	20	140	155
GHCE	012	30	168	200
GHCE	012	35	198	210

