

Product features

- The main body is made of aluminum die casting
- The reflector is anodized alumina
- The main body is available in black and white
- Can choose dimming or not dimming

Applications

- Offices, shopping malls, schools, factories, houses, etc

Technical Parameters

- Light type : LED
- Lamp Base Type : LED
- Lamp power : 10-40W
- Electrical type: switching power supply
- Power supply: 220V ~ 240V, 50Hz

- Protection: IP54
- Insulation Class: Class 1
- Safety Standards: IEC 598



Ordering guide:

GHSD	007	1			DA				220	
Model	lights QTY		Dimensions		Power Supply		Mounting		Color temperature	
GHSD	1 one Please refer to the technical information of light source		90 Ø90*H90 110 Ø110*H120 130 Ø130*H152 170 Ø170*H185 193 Ø193*H193		SP Switch Power Supply DALI DALI Dimmable Driver Triac Triac Dinnable Driver 1-10V 1-10V Dimmable Driver		CI Ceiling installation		YL 2700-3000K NL 3500-4200K WL 6000-6500K	
Number		Light Source		Design		Reflector		Voltage		
007		10 7-10W 15 12-15W 20 18-20W 30 25-30W 40 35-40W		DA Die casting aluminum		AL Aluminum		220 220-240V		

Remark: compliance with the requirement of the buyer

Model	Number	lights QTY	Light source power(W)	Diameter(mm)
GHSD	007	1	7-10W	Ø90*H90
GHSD	007	1	12-15W	Ø110*H120
GHSD	007	1	18-20W	Ø130*H152
GHSD	007	1	25-30W	Ø170*H185
GHSD	007	1	25-30W	Ø193*H193
GHSD	007	1	35-40W	Ø193*H193

